

UP Workstation SYS-551A-T

UP full rackmount tower workstation for product design and engineering simulation



More details here

Key Applications

Product Design and Engineering Simulation,

Key Features

- Socket E (LGA4677) support Intel® Xeon® W-3400 processors;
- Intel® W790;
- 16 DIMMs;
- 1x 1GbBaseT, 1x 10GbBaseT;
- 2 2.5" SATA3 drive bays; 4 3.5" SATA3 drive bays; ; 4 M.2 NVMe;
- 1 120 mm Fan(s) ; 2 120 mm Fan(s);
- 2000W Power Supplies Platinum Level (%+);



Form Factor	5U (Full Tower) Rackmount Enclosure: 222 x 535 x 573mm (8.74" x 21.06" x 22.56") Package: 372 x 708 x 724mm (14.6" x 27.8" x 28.5")
Processor	Single Socket E (LGA-4677) Intel® Xeon® W-3400 processors
GPU	Max GPU Count: Up to 2 quad-width or 2 triple-width or 4 double-width or 4 single-width GPU(s) Supported GPU: NVIDIA PCIe: T1000, RTX A6000, RTX A5000, RTX A4500, RTX A4000, RTX A2000, RTX 6000 ADA, RTX 4090, RTX 4080
System Memory	Slot Count: 16 DIMM slots Max Memory (2DPC): Up to 2TB 4800MT/s ECC DDR5 RDIMM/LRDIMM
Drive Bays Configuration	Default: Total 4 bay(s) • 4 internal fixed 3.5" SATA drive bay(s) M.2: 4 M.2 PCIe 5.0 x4 NVMe slot(s) (M-key 2280/22110) Peripheral Bays: 2 5.25" bay(s)
Expansion Slots	Default • 6 PCIe 5.0 x16 FHFL slot(s)
On-Board Devices	SATA: SATA (6Gbps) Chipset: Intel® W790 Network Connectivity: 1 RJ45 10GbE with Marvell® AQC113 1 RJ45 1GbE with Intel® I210-AT
Input / Output	USB: 2 USB 2.0 port(s) (rear) 2 USB 2.0 Type-A port(s) (front) 2 Type-A port(s) (Front) Video: 1 VGA port(s)



System Cooling	Fans: 1x 120mm Fan(s) 2x 120mm Fan(s)
Power Supply	1x 2000W Platinum Level power supply
System BIOS	BIOS Type: AMI 256MB SPI Flash
Management	SuperCloud Composer; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); SuperDoctor® 5; Super Diagnostics Offline ; TAS: Supermicro Thin-Agent Service (TAS); SAA(new!)
PC Health Monitoring	Voltage: +1.8V, +12V, +3.3V, +5V, +5V standby, 10 -fan status, 3.3V standby, HT, Memory, VBAT
Dimensions and Weight	Weight: Gross Weight: 39 lbs (17.74 kg) Net Weight: 20 lbs (14.9 kg) Available Color: Black
Operating Environment	Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)
Motherboard	<u>Super X13SWA-TF</u>
Chassis	<u>CSE-GS7A-2000B</u>